



**Version with Markings to**  
**Show Changes Made**

TITLE OF THE INVENTION

APPARATUS AND METHOD FOR CREATING DISTRIBUTION CONTENT

BACKGROUND OF THE INVENTION

5 Field of the Invention

[0001] The present invention relates to distribution content creating apparatuses and, more specifically, to a distribution content creating apparatus for creating a video or music content which is provided with use conditions.

10

Description of the Background Art

[0002] In recent years, content distribution services have become available for distributing video or music contents to terminals such as personal computers and portable phones. In such  
15 a content distribution service, a content (content body) is not simply distributed by itself. In order to prevent an illegal copy of the content body, the content body is provided with conditions restricting the use of the content body, thereby forming a content for distribution (distribution content). In consideration of the  
20 foreseeable expansion of the content distribution service, it is urgently required to develop distribution content creating apparatuses which are capable of efficiently creating various distribution contents.

[0003] A conventional distribution content creating apparatus  
25 creates a distribution content according to ~~in~~ the following

procedure. That is, the conventional apparatus stores content bodies, and edits management data for the respective content bodies. Then, the generated management data is provided to the content body, and the resulting content is the distribution content,  
5 which is ~~and~~ handled as a package.

[0004] The management data that is edited by the conventional apparatus includes data indicating conditions for the use of the content body at destination terminals, such as "playable only when a fee is paid", and "playable within a certain period". In the  
10 conventional apparatus, such management data is generated and provided to the respective content bodies.

[0005] The distribution content that is created in the above-described ~~above~~ manner is temporarily stored in the distribution content creating apparatus, and is then forwarded  
15 to a distributing apparatus. The distributing apparatus distributes the forwarded distribution content to a terminal through a network. The terminal receives the distribution content, and replays the content body according to the management data which is provided to the content.

20 [0006] As described above, the conventional distribution content creating apparatus creates a distribution content including a content body which is provided with conditions restricting the use of the content body at the terminals. Therefore, for example, it is possible to distribute a promotion distribution  
25 content that is playable for free only within a predetermined period

and a full-package distribution content that is playable upon payment of a fee.

[0007] In the conventional distribution content creating apparatus, one piece of management data is provided for each content body. Therefore, replay restriction and billing can be disadvantageously made only by the unit of the content body. If ~~such~~ a distribution content such as one that is provided with conditions that are effective only to part of the content body can be created, the distribution content will be usable for various purposes which have not been ~~never~~ achievable so far, hopefully leading to a boost in sales of contents through distribution.

[0008] Another disadvantage of the conventional apparatus is that different distribution contents have to be created for different purposes for the same content body, and stored in the apparatus. For example, a promotion distribution content and a full-package distribution content have to be created and stored for the same content body. Therefore, the same content body is redundantly stored, thereby wasting a large amount of storage. At the terminal side, if the user desires to try the content first before purchase, the user has to first receive the promotion distribution content, and then further receive the full-package ~~one~~ distribution content. This means that the user has to redundantly receive the same content body, thereby wasting time and communications cost.

## SUMMARY OF THE INVENTION

[0009] Therefore, an object of the present invention is to provide an apparatus which is capable of creating a distribution content provided with a condition that is only effective to part  
5 of a content body.

[0010] Another object of the present invention is to provide an apparatus which is capable of creating a distribution content including a content body that is provided with a plurality of conditions respectively corresponding to various use purposes.  
10 The present invention has the following features to attain the objects described above.

A first aspect of the present invention is directed to a distribution content creating apparatus that includes:

content storage means for storing content bodies;  
15 distribution content creating means for creating a distribution content by reading a content body from the content storage means and providing the content body with a use condition;  
and

content storage means for storing the distribution  
20 content which is created by the distribution content creating means. ~~wherein~~

Further, in the distribution content creating apparatus of the first aspect, the distribution content creating means includes management data editing means for editing management data  
25 indicating the use condition which is effective to a specific

section of the read content body, and\_

\_\_\_\_\_the distribution content creating means creates the distribution content by providing the content body with at least one piece of management data which is edited by the management data editing means.

[0011] In the first aspect (also in the following tenth and eleventh aspects), a specific section of the content body is defined, and management data indicating the use condition which is only effective to the specified section is edited. Then, the management data is provided to the content body for distribution. Thus, it is possible to create a distribution content provided with the use condition which is only effective to part of the content body.

[0012] The above created distribution content is stored in the distribution content creating apparatus, and is then distributed by a distributing apparatus to a terminal. The terminal receives and stores the distribution content, and then reads the distribution content ~~it~~ for replay. When replaying the distribution content, the terminal replays the specific section of the content body based on the management data.

[0013] According to a second aspect of the present invention, in accordance with the first aspect, \_\_\_\_\_the use condition that is indicated by the management data prohibits the use of the section which is specified by the management data, allows the use of the section which is specified by the management data for free, or allows the use of the section

which is specified by the management data in return for the payment of a predetermined fee.

[0014] In the above-described ~~above~~-second aspect, a specific section of the content body is defined, and can be set so that  
5 the terminal is prohibited from using ~~it~~ the specific section of the content body, or so that the terminal is allowed to use it the specific section of the content body for free or upon payment of a fee.

[0015] According to a third aspect, in accordance with the first  
10 aspect, \_

\_\_\_\_\_the management data further indicates a replay order of the section which is specified by the management data.

[0016] In the above-described ~~above~~-third aspect, the terminal can arbitrarily set the order of replaying the sections.

15 [0017] According to a fourth aspect of the present invention, in accordance with the first aspect, \_

\_\_\_\_\_the distribution content creating means creates the distribution content by further providing the content body with a plurality of pieces of management track data, and \_

20 \_\_\_\_\_each piece of management track data defines a collection of at least one piece of the management data indicating at least one section which is used for a predetermined purpose as one management track corresponding to the predetermined purpose.

[0018] In the above-described ~~above~~-fourth aspect, it is  
25 possible to create a distribution content including a content body

which is provided with a plurality of pieces of management track data corresponding to various use purposes (for example, for a promotion purpose where the content body is allowed to be only partly used for free, or for a full-package purpose where the entire content body is allowed to be used upon payment of a fee). Consequently, as compared with the conventional apparatus that creates different distribution contents for different use purposes, the redundancy of storing the same content body can be eliminated, thereby saving the storage amount of the distribution content creating apparatus side and the terminal side, and also reducing the cost of communications cost at the time of distribution. Furthermore, only one distribution content is enough to be received by the terminal side for using the content body for a user's desired purpose.

15 [0019] According to a fifth aspect of the present invention, in accordance with the fourth aspect, \_

\_\_\_\_\_the apparatus further includes character input means for supplying a character input, + and \_

\_\_\_\_\_GUI input means for supplying a GUI input. According  
20 to the fifth aspect, ~~wherein~~

\_\_\_\_\_the management data editing means makes a GUI screen be displayed, where the GUI screen includes including a plurality of management tracks that are provided along a time axis, and

\_\_\_\_\_the management data editing means edits the management  
25 data of the specific section by receiving, through the character

input means, a start time and an end time for defining the specific section of the content body on the time axis, and the use condition for the predetermined purpose. Further, and

\_\_\_\_\_the management data editing means places, based on the  
5 edited management data, a bar on the management track corresponding to the purposes in the GUI screen.

**[0020]** In the above-described ~~above~~-fifth aspect, for each content use purpose (for example, for a promotion purpose where the content body is allowed to be only partly used for free, or  
10 for a full-package purpose where the entire content body is allowed to be used upon payment of a fee), a start time and an end time for defining a section on the time axis, and a use condition are inputted as character inputs, thereby editing the management data for that section. Then, based on the management data which is  
15 obtained for each purpose, a bar corresponding to each section (the bar with one end located at the start time and the other end located at the end time) is placed on the management track corresponding to the purpose in the GUI screen.

**[0021]** According to a sixth aspect of the present invention,  
20 in accordance with the fifth aspect, \_

\_\_\_\_\_the distribution content creating means further includes management data storage means for storing the management data that is edited by the management data editing means.

**[0022]** In the above-described ~~above~~-sixth aspect, the  
25 management data is stored separately from the distribution content



including the content body which is provided with the management data.

**[0023]** According to a seventh aspect of the present invention,  
in accordance with the sixth aspect, \_

5 \_\_\_\_\_the management data editing means reads the management data previously edited from the management data storage means, and places, based on the read management data, a bar on the management track in the GUI screen. Further, and

\_\_\_\_\_the management data editing means edits the management  
10 data by moving one end and/or the other end of the bar along the time axis through an operation by the GUI input means.

**[0024]** In the above-described ~~above~~ seventh aspect, when the management data is edited, a bar is displayed on the management track of the GUI screen based on the management data which was  
15 previously edited. Then, by moving either or both of the ends of the bar by the GUI input means, the management data is edited. This saves the operator from having to supply the trouble of  
~~supplying~~ character inputs.

**[0025]** According to an eighth aspect of the present invention,  
20 in accordance with the fourth aspect, \_

\_\_\_\_\_the distribution content creating means further includes replay means for reading the distribution content from the distribution content storage means and replaying, based on the management data, the specific section of the content body.

25 **[0026]** In the above-described ~~above~~ eighth aspect, the operator

of the distribution content creating apparatus can check how the distribution content will be replayed at the terminal side.

[0027] According to a ninth aspect of the present invention, in accordance with the eighth aspect, \_

5 \_\_\_\_\_the replay means selects one of the plurality of pieces of management track data that is included in the read distribution content and, based on at least one piece of the management data which is included in the management track that is defined by the management track data, ~~and~~ replays at least one specific section  
10 of the content body.

[0028] In the above-described ~~above~~ ninth aspect, when the operator specifies the use purpose, the management track corresponding to the specified purpose is selected. Then, based on the management data that is included in the management track,  
15 a specific section of the content body is replayed. Thus, the operator of the distribution content creating apparatus can check how the distribution content will be replayed at the terminal side for each purpose.

[0029] A tenth aspect of the present invention is directed to  
20 a method of creating a distribution content including a content body which is provided with a use condition. The ~~and the~~ method of the tenth aspect includes:

a step of storing content bodies;

a step of creating a distribution content ~~(20)~~ by reading  
25 a content body which is stored in the content body storing step

and providing the content body with the use condition; and

a step of storing the distribution content created in the distribution content creating step. Further, wherein

~~\_\_\_\_\_~~in the distribution content creating step, \_

5 ~~\_\_\_\_\_~~management data indicating the use condition for a specific section of the content body is edited, and \_

~~\_\_\_\_\_~~the distribution content is created by providing the content body with at least one piece of the edited management data.

**[0030]** An eleventh aspect of the present invention is directed

10 to a content distribution system that includes:

a distribution content creating apparatus for creating a distribution content including a content body which is provided with a use condition;

a distributing apparatus for distributing the  
15 distribution content which is created by the distribution content creating apparatus; and

a terminal for receiving and using the distribution content which is distributed by the distributing apparatus, wherein

The ~~the~~ distribution content creating apparatus of the  
20 eleventh aspect includes:

—content storage means for storing content bodies;

—distribution content creating means for creating the distribution content by reading a content body from the content storage means and providing the content body with the use condition;

25 and

—first distribution content storage means for storing the distribution content which is created by the distribution content creating means.~~7~~

Further, the distribution content creating means  
5 includes management data editing means for editing management data indicating the use condition for a specific section of the content body, and

————the distribution content creating means creates the distribution content by providing the content body with at least  
10 one piece of the management data which is edited by the management data editing means.~~7~~ ~~and~~

The ~~the~~ terminal of the eleventh aspect includes:

—receiving means for receiving the distribution content which is distributed by the distributing apparatus;

15 —second distribution content storage means for storing the distribution content received by the receiving means; and

—replay means for reading the distribution content from the second distribution content storage means, and replaying,  
20 based on the management data, the specific section of the content body.

**[0031]** A twelfth aspect of the present invention is directed to a terminal for receiving and using a distribution content including a content body, and management data indicating a use  
25 condition for a specific section of the content body. The ~~7~~ ~~and~~

~~the terminal of the twelfth aspect~~ includes:

receiving means for receiving the distribution content;

distribution content storage means for storing the  
distribution content which is received by the receiving means;

5 and

replay means for reading the distribution content from  
the distribution content storage means, and replaying, based on  
the management data, the specific section of the content body.

[0032] In the above-described ~~above~~ twelfth aspect, at least  
10 one section which is specified by at least one piece of management  
data that is included in the distribution content is replayed  
according to the condition which is specified by the management  
data.

[0033] According to a thirteenth aspect of the present invention,  
15 in accordance with the twelfth aspect, \_

\_\_\_\_\_the use condition which is indicated by the management  
data prohibits the use of the section that is specified by the  
management data, allows the use of the section that is specified  
by the management data for free, or allows the use of the section  
20 that is specified by the management data in return for payment  
of a predetermined fee. Further, according to the thirteenth  
aspect,

\_\_\_\_\_the terminal further comprises billing means for billing  
based on the management data. ~~and~~

25 When ~~when~~ the use condition allows the use of the section

for free, the replay means replays the section, and when the use condition allows the use of the section in return for payment of the predetermined fee, the replay means replays the section after the billing means charges the fee.

5   **[0034]**     In the above-described ~~above~~-thirteenth aspect, each specific section of the content can be so set as to be prohibited from being used, or allowed to be used for free or upon payment of a fee. A particular ~~The~~ section is replayed if it is allowed to be used for free. On the other hand, if a particular section  
10 is ~~If~~ allowed to be used upon payment of a predetermined fee, such ~~a~~ ~~the~~ section is replayed after the fee is charged.

**[0035]**     According to a fourteenth aspect of the present invention, in accordance with the twelfth aspect, \_\_\_\_\_ the management data further indicates a replay order  
15 of the section which is specified by the management data, and \_\_\_\_\_ the replay means replays at least one section which is specified by the management data in the replay order that is indicated by the management data.

**[0036]**     In the above-described ~~above~~-fourteenth aspect, each  
20 section of the content body has a replay order set therein. The sections are replayed in a decreasing replay order.

**[0037]**     According to a fifteenth aspect of the present invention, in accordance with the twelfth aspect, \_\_\_\_\_ the distribution content further includes a plurality  
25 of pieces of management track data defining a collection of at

least one piece of the management data indicating at least one section which is used for a predetermined purpose as one management track corresponding to the purpose. Further, and  
\_\_\_\_\_the replay means selects one of the plurality of pieces  
5 of management track data that is included in the read distribution content and, based on at least one piece of the management data that is included in the management track defined by the management track data, replays at least one specific section of the content body.

10 **[0038]** In the above-described ~~above~~-fifteenth aspect, when the user specifies the use purpose, the management track corresponding to the use purpose is selected. Then, based on at least one piece of management data that is included in the management track, at least one specific section of the content is replayed. Thus, by  
15 receiving the distribution content only once, it is possible to use the content body for various purposes, such as for trying part of the content body for free and then using the entire content body by paying the fee.

**[0039]** A sixteenth aspect of the present invention is directed  
20 to a distribution content that includes\_+  
\_\_\_\_\_a content body, ~~+~~ and\_  
\_\_\_\_\_at least one piece of management data, wherein\_  
\_\_\_\_\_the management data indicates a use condition for a specific section of the content body.

25 **[0040]** In the above-described ~~above~~-sixteenth aspect, the

content body is provided with the management data indicating a use condition for a specific section of the content body, thereby forming a distribution content. The terminal receives such distribution content, and replays the specific section of the content body based on the management data.

[0041] According to a seventeenth aspect of the present invention, in accordance with the sixteenth aspect, the use condition which is indicated by the management data prohibits the use of the section that is specified by the management data, allows the use of the section that is specified by the management data for free, or allows the use of the section that is specified by the management data in return for payment of a predetermined fee.

[0042] In the above-described ~~above~~ seventeenth aspect, each specific section of the content can be so set as to be prohibited from being used, allowed to be used for free or allowed to be used upon payment of a fee. The terminal that receives the distribution content for use replays the section if the section ~~it~~ is allowed to be used for free and, if the section ~~it~~ is allowed to be used upon payment of a predetermined fee, replays the section after the fee is charged.

[0043] According to an eighteenth aspect of the present invention, in accordance with the sixteenth aspect, the management data further indicates a replay order of the section which is specified by the management data.



[0044] In the above-described ~~above~~-eighteenth aspect, each section of the content body has a replay order set therein. The sections are replayed in a decreasing replay order.

[0045] In a nineteenth aspect of the present invention, in  
5 accordance with the sixteenth aspect, —  
—the distribution content further includes a plurality  
of pieces of management track data, wherein —  
—each piece of management track data defines a collection  
of at least one piece of the management data indicating at least  
10 one section which is used for a predetermined purpose as one  
management track corresponding to the purpose.

[0046] In the above-described ~~above~~-nineteenth aspect, the  
content body is provided with a plurality of pieces of ~~of~~ management  
track data respectively corresponding to various use purposes.  
15 When the user specifies the use purpose, the terminal that receives  
the distribution content for use selects the management track  
corresponding to the specified use purpose. Then, based on at  
least one piece of management data that is included in the management  
track, the terminal replays at least one specified section of the  
20 content body.

[0047] These and other objects, features, aspects and  
advantages of the present invention will become more apparent from  
the following detailed description of the present invention when  
taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

**[0048]** FIG. 1 is a block diagram illustrating the structure of a content distribution system according to one embodiment of the present invention;

5 FIG. 2 is a flowchart showing outlines of the operation of the content distribution system of FIG. 1;

FIG. 3 is a block diagram illustrating the functional structure of a distribution content creating apparatus 1 of FIG. 1;

FIG. 4 is a diagram illustrating the data structure of a distribution content which is created by a distribution content  
10 creating unit 13 of FIG. 4;

FIG. 5 is a diagram showing one example of header information which is included in a header portion of FIG. 4;

FIG. 6 is a diagram illustrating one example of management track data which is included in a management track  
15 portion of FIG. 4;

FIG. 7 is a diagram illustrating one example of management data which is included in the management track portion of FIG. 4;

20 FIG. 8 is a block diagram illustrating one example of the hardware structure of the distribution content creating apparatus 1 of FIG. 1;

FIG. 9 is a flowchart showing a management data editing process (detailed process of step S1 in FIG. 2) which is carried  
25 out by the distribution content creating apparatus 1 structured

as shown in FIG. 3;

FIG. 10 is a diagram illustrating one example of a GUI screen that is displayed on a display unit 16 by following an instruction from a management data editing part 131 of FIG. 3;

5        FIG. 11 is a diagram illustrating one example of a character input screen that is displayed on the display unit 16 by following an instruction from the management data editing part 131 of FIG. 3;

10        FIG. 12 is a diagram illustrating one example of a management data selection screen that is displayed on the display unit 16 by following an instruction from the management data editing part 131 of FIG. 3;

15        FIG. 13 is a flowchart showing a distribution content replay process (detailed process of step S4 in FIG. 2) which is carried out by the distribution content apparatus 1 structured as shown in FIG. 3;

FIG. 14 is a block diagram illustrating one example of the structure of a terminal 4 of FIG. 1;

20        FIG. 15 is a flowchart showing a distribution content replay process (detailed process of step S8 in FIG. 2) which is carried out by the terminal 4 structured as shown in FIG. 14;

FIG. 16 is a flowchart showing a detailed process of step S304 of FIG. 15; and

25        FIG. 17 is a diagram showing how a replay unit 44 replays data for respective sections in the order which is specified by

management data 208 to 210.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

**[0049]** ~~One~~ ~~With reference to the drawings, described below is~~  
5 ~~one~~ embodiment of the present invention will now be described with  
reference to the drawings.

FIG. 1 is a block diagram illustrating the structure  
of a content distribution system according to one embodiment of  
the present invention. In FIG. 1, the present content distribution  
10 system includes a distribution content creating apparatus 1, a  
distributing apparatus 2, a network 3, and a terminal 4.

**[0050]** The distribution content creating apparatus 1 edits  
management data for a content body to be distributed, and provides  
the management data to the content body for creating a distribution  
15 content. Here, a "content body" is video such as a movie, or audio  
such as a piece of music. The "management data" is data indicating  
conditions for replaying the content body (the details of which  
are described later). The "distribution content" is a package  
including a content body which is provided with management data.

20 **[0051]** The distributing apparatus 2 distributes the  
distribution content through the network 3 to the terminal 4. The  
network 3 is a medium for transferring the distribution content  
from the distributing apparatus 2 to the terminal 4, and is  
implemented by, for example, a communications network such as the  
25 Internet or a portable phone network, or a broadcast network such

as a satellite broadcast network.

[0052] The terminal 4 receives and replays the distribution content. At this time, the terminal 4 replays the content body based on the management data provided therewith. The terminal  
5 4 is typically implemented by a general-purpose personal computer or a portable phone but, ~~alternatively,~~ the terminal 4 may alternatively be a terminal which is dedicated to the present system.

[0053] With reference to a flowchart of FIG. 2, outlines of  
10 the operation of the above-structured content distribution system are described below.

FIG. 2 is a flowchart showing the outlines of the operation of the content distribution system of FIG. 1. In FIG. 2, the distribution content creating apparatus 1 stores content bodies,  
15 and edits management data for the respective content bodies on management tracks (step S1). Then, the distribution content creating apparatus 1 provides the management data which is edited in step S1 to the respective content bodies together with management track data for creating a packaged distribution content (step S2).

20 [0054] The distribution content which is created in the above-described ~~above~~ manner is temporarily stored in the distribution content creating apparatus 1 (step S3). Then, the distribution content is replayed for checking ~~check~~ at the distribution content creating apparatus 1 side (step S4). Then,  
25 the distribution content is forwarded to the distributing apparatus

2 (step S5).

The distributing apparatus 2 distributes the received distribution content through the network 3 to the terminal 4.

The terminal 4 receives the distribution content (step 5 S6), and then stores ~~it~~ the received distribution content (step S7). The terminal 4 then reads the distribution content in response to a user's instruction, and replays the content body by following the management data provided thereto (step S8).

**[0055]** ~~The Described next in detail is the~~ structure and operation of the distribution content creating apparatus 1 of FIG. 1 will now be described in detail (steps S1 to S4 of FIG. 2).

FIG. 3 is a block diagram showing the functional structure of the distribution content creating apparatus 1 of FIG. 1. In FIG. 3, the distribution content creating apparatus 15 1 includes a content storage unit 11, a distribution content storage unit 12, a distribution content creating unit 13, a character input unit 14, a GUI (graphical user interface) input unit 15, a display unit 16, and a replay unit 17. The distribution creating unit 13 includes a management data editing part 131 and a management data storage part 132. 20

**[0056]** The content storage unit 11 stores content bodies. The character input unit 14 receives ~~a~~ a character input by an operator (user). The GUI input unit 15 receives a GUI input by the operator. The distribution content creating unit 13 reads a content body 25 from the content storage unit 11, edits management data for the

content body, and provides the edited management data to the content body for creating a distribution content.

[0057] At this time, in the distribution content creating unit 13, the management data editing part 131 makes the display unit 16 display a screen for editing by GUI as shown in FIG. 10 (described later), a screen for character input as shown in FIG. 11 (described later), and a screen for management data selection as shown in FIG. 12 (described later). The management data editing part 131 then edits the management data in response to an input operation by the operator through the respective screens. The management data editing part 131 then stores the edited management data in the management data storage unit 132.

[0058] Assuming that the content body is used for a plurality of purposes, the distribution content creating unit 13 edits the management data on a plurality of management tracks corresponding to the respective purposes. The distribution content creating unit 13 then generates a plurality of pieces of management track data defining, as a management track, a collection of at least one piece of management data indicating at least one section which is used for the same purpose. The distribution content creating unit 13 then provides the management data and the management track data to the content body for creating a distribution content, and stores the created distribution content ~~it~~ in the distribution content storage unit 12.

[0059] In other words, the distribution content (content body

+ management track data + management data) which is created by the distribution content creating unit 13 is stored in the distribution content storage unit 12, and, in addition, ~~also~~ the management data is separately stored in the management data storage part 132 of the distribution content creating unit 13.

[0060] ~~The Here, the~~ data structure of the distribution content will now be ~~is~~ described. FIG. 4 is a diagram illustrating one example of the data structure of the distribution content which is created by the distribution content creating apparatus 1 of FIG. 1. In FIG. 4, a distribution content 20 includes a header portion 21, a content portion 22, and a plurality of management track portions 23. The header portion 21 includes header information 24 indicating the data structure of the distribution content 20. The content portion 22 includes a content body 25. Each management track portion 23 includes one piece of management track data 26 and one or more pieces of management data 27.

[0061] FIG. 5 is a diagram illustrating one example of the header information 24 which is included in the header portion 21 of FIG. 4. In FIG. 5, the header information 24 contains "totalSize" indicating the total data size of the distribution content 20, "pContentData" indicating a pointer to the content body 25, "contentDataSize" indicating the data size of the content body 25, "numTrack" indicating the number of management tracks, "defaultTrackNo" indicating a default track number, "pTrack" indicating a pointer to the head management track portion 23, and



"trackSize" indicating the size of the head management track portion 23.

[0062] FIG. 6 is a diagram illustrating one example of the management track data 26 which is included in the management track portion 23 of FIG. 4. In FIG. 6, the management track data 26 contains "numData" indicating the total number of pieces of management data 27 that are included in the management track portion 23, "pOffsetData" indicating a pointer to the header management data 27, and "dataSize" indicating the size of the management data 27.

[0063] FIG. 7 is a diagram illustrating one example of the management data 27 which is included in the management track portion 23 of FIG. 4. In FIG. 7, the management data 27 contains "inTime" indicating a start time, "outTime" indicating an end time, "playtype" indicating a replay condition, "finacialtype" indicating a billing condition, and "playorder" indicating a replay order.

[0064] Referring back to FIG. 3, the replay unit 17 is provided for checking how the distribution content which is created in the above-described ~~above~~ manner will be replayed by the terminal 4. In response to an instruction by the operator through the GUI input unit 15, the replay unit 17 ~~15~~ reads the distribution content from the distribution content storage unit 12 for replay, and outputs the read distribution content ~~it~~ to the display unit 16.

[0065] FIG. 8 is a block diagram illustrating one example of

the hardware structure of the distribution content creating apparatus 1 of FIG. 1. In FIG. 8, the distribution content creating apparatus 1 includes a CPU 101, a ROM 102, a RAM 103, a sound/video board 104, ~~and~~ a hard disk (HD) 105, a keyboard 106, a mouse 107, a monitor 108, and a loudspeaker 109.

In FIG. 3, the content storage unit 11 and the distribution content storage unit 12 are implemented by the hard disk 105; the character input unit 14 is implemented by the keyboard 106; the GUI input unit 15 is implemented by the mouse 107; and the display unit 16 is implemented by the monitor 108 and the loudspeaker 109.

[0066] The distribution content creating unit 13 is implemented by the CPU 101, the ROM 102, and the RAM 103. That is, upon ~~on~~ receiving an instruction that is provided by the user through the keyboard 106 and/or the mouse 107, the CPU 101 operates by following predetermined content creating program data which is previously stored in the ROM 102. The RAM 103 is used as a working area when the CPU 101 operates.

[0067] The replay unit 17 is implemented by the CPU 101, the ROM 102, the RAM 103, and the sound/video board 104. That is, upon ~~on~~ receiving an instruction that is provided by the user through the keyboard 106 and/or the mouse 107, the CPU 101 controls the sound/video board 104 by following a predetermined content replay program data which is previously stored in the ROM 102. The RAM 103 is used as a working area when the CPU 101 and the sound/video

board 104 operate.

[0068] Here, the above-described ~~above~~ content creating/replay program data may be provided as being stored in a portable recording medium such as CD-ROM, instead of being  
5 previously stored in the ROM 102. Alternatively, the program data may be provided to the distribution content creating apparatus 1 through the network. The program data provided as such is loaded in the hard disk 105, and is then forwarded to the RAM 103 at the time of content creation/replay.

10 [0069] FIG. 9 is a flowchart showing a management data editing process (a detailed process of step S1 in FIG. 2) which is carried out by the distribution content creating apparatus 1 structured as shown in FIG. 3.

In the distribution content creating apparatus 1, a  
15 plurality of content bodies are stored in the content storage unit 11. When the distribution content creating apparatus 1 is activated, the management data editing part 131 first makes the display 16 display ~~such a~~ GUI screen such as the one shown in FIG. 10 (step S101).

20 [0070] Here, FIG. 10 is a diagram illustrating one example of the GUI screen which is displayed on the display 16 by following an instruction from the management data editing part 131 of FIG. 3. On the GUI screen of FIG. 10, a content track 205 and one or more management tracks are displayed along a time axis 204. At  
25 first, only one management track is displayed (here, "management

track 1" 207), and then one or more new tracks are additionally displayed according to a request from the operator (here, "management track 2" 211, and "management track 3" 213). On the content track 205, a content body 206 is displayed as a bar having  
5 a length which is in proportion to its replay time. Also, on the content body 206, two separation lines (dotted lines 216 and 217 ~~in the drawing FIG.10~~) are displayed for defining a section. The separation lines 216 and 217 are moved in a direction of the time axis in response to an operation of the mouse 107 (GUI input unit  
10 15) by the operator (~~in the drawing FIG.10~~, the separation lines are positioned at t1 and t2, respectively).

[0071] On the management tracks 207, 211, and 213, short bars are displayed along the content body 206 which appears ~~appeared~~ on the content track 205, based on management data corresponding  
15 to the section that is defined by the ~~above~~ above-mentioned separation lines. For example, on the "management track 1" 207, a short bar 208 is displayed based on management data for a section from t1 to t2 that is defined by the separation lines 216 and 217.

[0072] On an upper portion of the GUI input screen of FIG. 10,  
20 four buttons are displayed. When a "button 1" 200 is clicked, a character input screen as shown in FIG. 11 (described later) is further displayed on the display unit 16. When a "button 2" 201 is clicked, the two separation lines 216 and 217 are displayed on the content track 205, indicating start and end times,  
25 respectively, inputted though the above-described ~~above~~ character

input screen. When a "button 3" 202 is clicked, a new management track is additionally displayed. When a "button 4" 203 is clicked, a management data selection screen as shown in FIG. 12 (described later) is further displayed on the display unit ~~13~~ 16.

5   **[0073]**     When a ~~such~~ GUI screen such as the one described above is displayed (presenting, at this moment, the four buttons 200 to 203, the time axis 204, and the content track 205), the operator clicks the "button 1" 200 through the GUI input unit 15. In response, the management data editing part 131 makes the display  
10   unit 16 display ~~such a~~ character input screen such as the one shown in FIG. 11 (step S102).

**[0074]**     ~~Here,~~ FIG. 11 is a diagram illustrating one example of the character input screen which is displayed on the display unit 16 by following an instruction from the management data editing  
15   part 131 of FIG. 3. Displayed on the character input screen shown in FIG. 11 are a start time (*in*) field 301 and an end time (*out*) field 302 which each for specifying specify a section of the content body, a replay condition field 303 for entering a replay condition for the specified section, a billing condition field  
20   304 for entering a billing condition for the specified section, and a replay order field 305 for entering a replay order of the specified section.

**[0075]**     When a ~~such~~ GUI screen such as the one described above is displayed, the operator enters desired times (for example, times  
25   t1 and t2) in the *in* field 301 and the *out* field 302, respectively,

through the character input unit 14. Also, the operator enters desired conditions (for example, the operator enters "conditional replay" and "200 yen") in the replay condition field 303 and the billing condition field 304, respectively. That is, the section from t1 to t2 of the content body can be replayed if 200 yen is paid. Furthermore, the operator enters a replay order (for example, "first" if the section should be replayed first) in the replay order field 305.

**[0076]** In response, the management data editing part 131 sets management data indicating the entered replay conditions (in this example, "first", "conditional replay", and "200 yen") for the section specified in the content body (in this example, the section from t1 to t2) (step S103).

**[0077]** The operator then clicks the "button 2" 201 on the GUI screen. In response, based on the management data indicating that replay conditions including "first", "conditional replay", and "200 yen" are set in the section from t1 to t2, the management data editing part 131 makes the short bar 208 be displayed in the section from t1 to t2 on the "management track 1" 207 of the GUI screen. The management data editing part 131 then stores the management data for the short bar 208 which is set in step S103 in the management data storage 132 (step S105).

**[0078]** Thus, one piece of management data which is represented by the short bar 208 has been set to the content body on the "management track 1" 207. If the operator desires to end the

management data editing process, all he/she has to do is to give an instruction for ending the editing process. If the operator desires to set management data for another section on the "management track 1" 207, he/she again uses the GUI input unit 15, clicking the "button 1" 200 ~~201~~ through to make the character input screen be displayed, and carries out the same setting process as described above. If the operator desires to set management data on the "management track 2" 211, he/she clicks the "button 3" 202 to display another "management track 2" 211 for carrying out the same setting process as described above.

**[0079]** The management data editing part 131 carries out a series of the following processes based on an input operation by the operator as described above. First, the management data editing part 131 determines whether to continue the editing process (step 15 S106). If No in step S106, the editing process ends, and the procedure returns to the flowchart flow of FIG. 2 for steps S2 and thereafter.

If Yes in step S106, the management data editing part 131 determines whether to set management data for another section on 20 the current management track (here, the "management track 1" 207) (step S107). If Yes in step S107, the procedure returns to step S102 for making ~~again~~ the character input screen be displayed again on the display unit 16, and then repeats the process as in steps S103 to S107.

25 **[0080]** If No in step S107, the management data editing part 131

makes a new management track (here, the "management track 2" 211) be additionally displayed (step S108). Then, when editing the new management data on the "management track 2" 211 which is displayed in step S108, the management data editing part 131 determines whether to use the management data which was previously edited and stored in the management data storage part 132 (for example, the management data corresponding to the short bar 208 which was stored in step S105) (step S109).

**[0081]** If Yes in step S109, the management data that is stored in the management data storage part 132 is copied to the new management track (here, the "management track 2" 211) which is displayed in step S108 (step S110).

**[0082]** ~~A Here, a~~ management data copy process of step S110 is carried out as follows, for example. When the operator clicks the "button 4" 203 on the GUI screen, the management data editing part 131 makes a management data selection screen such as the one shown in FIG. 12 be displayed on the display unit 16.

**[0083]** FIG. 12 is a diagram showing one example of the management data selection screen which is displayed on the display unit 16 by following an instruction from the management data editing part 131 of FIG. 3. In FIG. 12, the management data selection screen includes a table containing a plurality of pieces of management data which were previously edited (208, 211, ...) and their details (start/end time, replay order, replay and billing conditions). When the operator clicks any desired management data for use (for



example, the management data 208), the management data editing part 131 copies the bar representing the desired management data onto the "management track 2" 211 of the GUI screen (refer to FIG. 10), and also reads the details of the desired management data from the management data storage part 132.

**[0084]** The operator then specifies the in and out times by using the GUI input unit 15 so as to move the ends of the bar representing the management data which is displayed on the "management track 2" 211. In response, the management data editing part 131 sets a new piece of management data (step S111). The management data editing part 131 then stores the new management data which is set through the GUI input unit 15 in the management data storage part 132 (step S112). The management data editing part 131 then determines whether to continue the editing process (step S113). If No in step S113, the editing process ends, and the procedure returns to the flowchart flow of FIG. 2 for step S2 and thereafter.

If Yes in step S113, the procedure returns to step S107 for determining whether to set management data for still another section on the "management track 2" 211.

**[0085]** If No in step S109, the procedure returns to step S102 for making ~~again~~ the character input screen be displayed again on the display unit 16, and repeats the process of steps S103 to S109.

When the management data editing part 131 ends editing one or more pieces of management data on the respective management

tracks, the distribution content creating apparatus 2 executes step S2 of FIG. 2.

**[0086]** In step S2 of FIG. 2, the distribution content creating apparatus 1 generates management track data for defining a collection of one or more pieces of management data as a management track. The generated data of a plurality of management tracks and the management data that is edited by the management data editing part 131 are provided to the content body for creating a packaged distribution content.

10 **[0087]** In the next step S3, the distribution content creating apparatus 1 temporarily stores the above-created distribution content in the distribution content storage unit 12. Note that the management data which were previously edited and stored in the management data storage part 132 are used as required when  
15 the management data for another content is edited.

**[0088]** The distribution content creating apparatus 1 then carries out the process in the above-described ~~above~~ step S4 (refer to FIG. 2), that is, the distribution content replay process for checking the above-created distribution content.

20 **[0089]** FIG. 13 is a flowchart showing the distribution content replay process (details of step S4 in FIG. 2) which is carried out by the distribution content creating apparatus 1 structured as shown in FIG. 3.

In FIG. 13, the replay unit 17 first reads the  
25 distribution content from the distribution content storage unit

12 in response to an instruction from the operator through the GUI input unit 15 (step S201). Then, the replay unit 17 separates the read distribution content into the management track data, the management data, and the content body (step S202).

5   **[0090]**     After the operator specifies any one of the management tracks through the GUI input unit 15, the replay unit 17 reads the management track data corresponding to the specified track (step S203). Then, by following a clock signal, the replay unit 17 replays a specific section of the content body based on the  
10 management data which is included in the specified management track (step S204). The procedure then returns to the flowchart flow of FIG. 2.

**[0091]**     Here, the content replay process of the above-described  
~~above~~ step S204 is carried out as follows, for example. The content  
15 body is provided with a plurality of pieces of management track data that respectively correspond to different use purposes (for example, for a promotion purpose and a full-package purpose; described later) (refer to the management tracks 207 and 211 of FIG. 10). Therefore, the operator sequentially selects  
20 management tracks corresponding to a desired use purpose by using the GUI input unit 15. In response, the replay unit 17 replays the sections that are included in the content body and specified by the management data which is included in the selected management track in the order also specified by the management data.

25   **[0092]**     Thus, when the content body is distributed for a

promotion purpose or a full-package purpose, the operator of the distribution content creating apparatus 1 can check, for example, how the content body will be replayed by the terminal 4.

[0093] Each piece of management data includes the replay order, 5 replay/billing conditions, and start and end times defining a section to which the aforementioned ~~above~~ conditions are applied. Based on the clock signal that is given by the CPU 101 of FIG. 8, for example, and the above-described ~~above~~ replay order and start and end times, the replay unit 17 specifies the replay order 10 in the content body and the section to which the replay/billing conditions are applied. Based on the specified replay order and replay/billing conditions, the replay unit 17 replays the section.

[0094] Note that the replay unit 17 of the distribution content creating apparatus 1 does not replay a section for which the user 15 has to pay a fee which is specified by the management data. Such a section is replayed by the terminal 4 after the fee is charged (described later).

For example, if the section from t1 to t2 of the content body is provided with ~~such~~ a condition such as that the section 20 cannot be replayed until 200 yen is paid, the terminal 4 side replays this ~~the~~ section after billing is actually made. On the other hand, the creating apparatus 1 does not charge the terminal for the section or replay the section. Alternatively, the distribution content creating apparatus 1 may replay the section 25 regarding as if the fee is paid or as if the fee is not paid.

[0095] ~~The Described next in detail is the~~ structure and operation of the terminal 4 of FIG. 1 will now be described in detail.

FIG. 14 is a block diagram illustrating the structure of the terminal 4 of FIG. 1. In FIG. 14, the terminal 4 includes a receiving unit 41, a distribution content storage unit 42, a GUI input unit 43, a replay unit 44, a display unit 45, and a billing unit 46.

[0096] The receiving unit 41 receives a distribution content through the network 3. The distribution content storage unit 42 stores the distribution content which is received by the receiving unit 41. The GUI input unit 43 receives a GUI input from the user. The replay unit 44 is used for the user to view the distribution content in the above-described above described manner. In response to an instruction that is made by the user through the GUI input unit 43, the replay unit 3 reads the distribution content from the distribution content storage unit 12 for replay, and outputs the read distribution content ~~it~~ to the display unit 45. The billing unit 46 charges a bill of a predetermined amount to the user for the operation of the replay unit 44.

Note that the hardware structure of the terminal 4 is similar to that shown in FIG. 8.

[0097] In the above-structured ~~above-structure~~ terminal 4, the distribution content replay operation is carried out by the replay unit 44 as follows. FIG. 15 is a flowchart showing the distribution

content replay process (a detailed process of step S8 in FIG. 2)  
which is carried out by the terminal 4 structured as shown in FIG.  
14.

**[0098]** In FIG. 15, in response to an instruction that is given  
5 by the user through the GUI input unit 43, the replay unit 44 first  
reads a distribution content from the distribution content storage  
unit 42 (step S301). The replay unit 44 then separates the read  
distribution content into management track data, management data,  
and a content body (step S302).

10 **[0099]** After receiving an instruction indicating a management  
track that is specified by the user through the GUI input unit  
43, the replay unit 44 reads the management track data corresponding  
to the specified track (step S303). Based on the management data  
which is included in the specified management track, the replay  
15 unit 44 replays a specific section of the content body by following  
a clock signal (step S304). The procedure then returns to the  
flowchart flow of FIG. 2.

**[0100]** As such, the operation of the replay unit 44 which is  
included in the terminal 4 is similar to that of the replay unit  
20 17 which is included in the distribution content creating apparatus  
1 (refer to the flowchart of FIG. 13). However, the terminal 4  
side is different from the distribution content creating apparatus  
1 side in part of the content replay program that is stored in  
the ROM 102 shown in FIG. 8. In step S304, a bill is charged  
25 accompanying to the replay.

[0101] FIG. 16 is a flowchart showing the detailed content replay process of step S304 in FIG. 15. In FIG. 16, the replay unit 44 first selects management data of the highest replay order from the management data that is included in the specified management track (step S401). The replay unit 44 then determines whether the management data which is selected in step S401 allows for the use of a specific section for free (step S402). If No in step S402, the procedure goes to step S404.

[0102] If Yes in step S402, the replay unit 44 replays the section specified by the management data which is selected in step S401 (step S403). The procedure then goes to step S407.

[0103] In step S404, the replay unit 44 determines whether the management data which is selected in step S401 allows for the replay of the specific section in return for payment. If No in step S404, the procedure goes to step S407.

[0104] If Yes in step S404, the replay unit 44 notifies the billing unit 46 of the amount indicated by the management data which is selected in step S401, and then determines whether the indicated amount has been charged by the billing unit 46 (step S405). If No in step S405, the procedure goes to step S407.

[0105] Here, the above-described ~~above~~-billing process is carried out as follows, for example. The billing unit 46 accesses a host computer in a financial institution through the network 3, and transfers a specific amount from a user's account to a distributor's account. Alternatively, the billing unit 46 may

deduct the specific amount from a prepaid card which was previously  
purchased by the user, or record the specific amount and charge  
the amount ~~it~~ later on a predetermined date.

[0106] Referring back to FIG. 16, if Yes in step S405, the replay  
5 unit 44 replays the section specified by the management data which  
is selected in step S401 (step S406). The procedure then goes  
to step S407.

In step S407, it is determined whether all of the  
management data which are included in the specified management  
10 track have been selected. If Yes in step S407, the procedure  
returns to the flowchart flow of FIG. 15.

[0107] If No in step S407, the replay unit 44 selects management  
data of the next highest replay order from the management data  
which is included in the specified management track (step S408).  
15 The procedure then returns to step S402, repeating the operation  
similar to the one described above.

[0108] As clearly described ~~clear from the~~ above, the  
significant features of the distribution content creating process  
of the present invention can be categorized into the following  
20 six points. First, unlike the conventional one-to-one  
correspondence between the content body and the management data,  
the content body is divided into a plurality of sections on the  
time axis, and each section can be provided with ~~each~~ different  
management data. In other words, it is possible to specify a  
25 section in the content body, and to set management data to only



be effective to that section. This enables different replay conditions to be set to the respective sections. For example, a content body can be replayed only for the first few minutes, or can be replayed for free only for the first few minutes but the rest of the content body cannot be replayed unless a fee is paid.

[0109] Second, each management data includes a replay order, and therefore, the order of replaying the sections can be arbitrarily changed. For example, the three pieces of management data 208 to 210 on the "management track 1" 207 of FIG. 10 includes "first", "third", and "second", respectively. In this case, as shown in FIG. 17, the section from t1 to t2 in the content body 206 is first replayed, then the section from t5 to t6 is replayed, and then, the section from t3 to t4 is replayed.

15 [0110] Third, a plurality of tracks (207, 211, 213) are provided for the content track 205 on the GUI screen, thereby enabling different pieces of management data to be set for the same section of the content body. Thus, it is possible to obtain a distribution content whose content body can be used in a plurality of purposes. Specifically, a single content body can be distributed for a promotion purpose where the content body can be replayed only for a first few minutes for free and, at the same time, for a full-package purpose where the entire content body can be replayed.

[0111] As a result of achieving such distribution content including a single content body for a plurality of purposes, the

storage amount of the distribution content storage units 12 and 42 of the distribution content creating apparatus 1 side and the terminal 4 side, respectively, can be saved. Also, communications costs for distribution can be reduced. Furthermore, in the terminal 4 side, receiving only one distribution content is enough for the user to use the content body as he/she likes. Conventionally, the user has to receive two distribution contents, the promotion one and the full-package one, if he/she wants to try the content before purchasing such content~~purchase~~. In the present invention, the terminal 4 receives a distribution content, and then selects a management track by following a user's instruction. The terminal 4 then replays, in the order specified by the management data which is included in the selected management track, the sections also specified by the management data.

[0112] Fourth, the operator of the distribution content creating apparatus 1 can check how the distribution content will be replayed at the terminal 4 side. When a single distribution content is used for a plurality of purposes (two purposes, for example, a promotion purpose and a full-package purpose), it is possible to check how such distribution content will be replayed when used for the respective purposes.

[0113] Fifth, for editing management data, not only character inputs but also GUI inputs can be made. This greatly reduces the operator's workload.

Sixth, the management data which was previously edited

is stored, and can be used for editing new management data. This further reduces the operator's workload for editing.

[0114] ~~Specific Described next are specific examples of the~~  
distribution content creation operation which is carried out by  
5 the distribution content creating apparatus 1 will now be  
described.

~~(First Example example)~~

With reference to FIGS. 3, 10, 11, and 17, described below is a case of creating a promotion distribution content that  
10 is partly viewable for free. In the content storage unit 11 such as the hard disk 105, content bodies such as video data and music data are previously stored. The operator first selects a content body to be distributed from the stored content bodies. The selected content body is made to be displayed by the management data editing  
15 part 131 as the bar 206 which is placed on the content track 205 along the time axis 204 so that one end of the bar is placed at the origin of the time axis 204 in the GUI screen which is displayed on the display unit 16 (refer to FIG. 10).

[0115] The operator then operates the GUI input unit 15 such  
20 as the mouse 107 ~~by~~ clicking the "button 3" 202 on the GUI screen so as to display ~~for displaying~~ the "management track 1" for placing the management data. Furthermore, the operator clicks the "button 1" 200 for displaying the character input screen as shown in FIG. 11, and inputs use conditions at the time of content distribution.  
25 In this example, "unconditional replay" is inputted as the replay

condition, "free" is inputted as the billing condition, and "first" is inputted as the replay order. Furthermore, to specify a section of the content body to which the use condition is effective, an effective period is defined by the start time t1 and the end time t2, which are offset times from the replay start time of the content body. Based on the inputted management data, ~~displayed on the "management track 1" 207~~ is the bar 208 with its left end at the start time t1 and its right end at the end time t2 is displayed on the "management track"1 207.

10 [0116] In response to the operator's mouse 107 (GUI input unit 15) operation, the management data editing part 131 edits the start and end times of the management data by extending/shortening, in the time axis (lateral) direction, the bar 208 representing the inputted management data. Then, when the operator inputs 15 "unconditional replay", "free", t3 for the start time and t4 for the end time, and "third", the management data editing part 131 places a bar representing the inputted management data on an area between t3 and t4 of the "management track 1" 207. Furthermore, when the operator inputs "unconditional replay", "free", t5 for 20 the start time and t6 for the end time, and "second", the management data editing part 131 places a bar 210 representing the inputted management data on an area between t5 and t6 of the "management track 1" 207. Then, the management data editing part 131 stores the edited management data which is represented by the bars 208, 25 209, and 210 in the management data storage part 132. Note that,

in the present example, portions where no management data is arranged on the "management track 1" 207 cannot be replayed.

[0117] The edited content management data represented by the bars 208, 209, and 210 are packaged together with the content body, and stored in the distribution content storage unit 12 as a distribution content. The replay unit 17 then reads only data of the sections which are indicated by the management data corresponding to the bars 208, 209, and 210 as being replayable from the distribution content that is stored in the distribution content storage unit 12. Then, as shown in FIG. 17, data reproduction for the respective sections are carried out in the order as specified by the management data 208, 209, and 210, and the reproduction results are outputted to the display unit 16.

[0118] As such, in the present example, the management data is provided with the start time and the end time, thereby placing a plurality of pieces of management data on the same management track and editing these on the time axis. Thus, it is possible to easily create ~~such a~~ distribution content such as one ~~that~~ whose content body is intermittently replayed for a plurality of sections (for example, in a movie, only highlight scenes are replayed), which is typified by a promotion distribution content. Also, the management data is provided with the replay order, thereby replaying these sections (highlight scenes) in a desired order.

[0119] ~~(Second Example example)~~

With reference to FIGS. 3, 10 and 11, described below

is a case of creating a full-packaged distribution content whose entire content can be replayed upon the payment of a fee. In the present example, the distribution content having the management data for the a-promotion purposes created in the first example  
5 is provided with management data for a full-package purpose.

[0120] The operator first selects the distribution content (created in the above-described first-embodiment) which is stored in the distribution content storage unit 12. Based on the selected distribution content, the bar 206 is placed on the content track  
10 205 on the GUI screen as shown in FIG. ~~6~~ 10. Furthermore, ~~displayed on the "management track 1" 207~~ are the bars representing the promotion management data 208, 209, and 210 are displayed on the "management track 1" 207.

[0121] The operator then uses the GUI input unit 15, by clicking  
15 the "button 3" 202 on the GUI screen through so as to display for ~~displaying~~ a new "management track 2" 211 for placing a bar representing the management data for the full-package purpose below the "management track 1" 207. The operator clicks "button 1" 200 on the GUI screen in the similar manner as that in the first example  
20 for making the character input screen (refer to FIG. 11) be displayed on the display unit 16, and inputs replay conditions in the respective fields. Since the distribution content is for the full-package purpose in this example, the operator inputs "conditional replay" as the replay condition, a fee ("200 yen",  
25 for example) as the billing condition, and the start time (0) and

the end time (end). Based on the inputted management data, a bar 212 which is defined by the start and end times is displayed on the "management track 2" 211.

[0122] The full-package management data that is represented by the bar 212 and edited in the above-described ~~above-described~~ manner is added to the distribution content (including the content body, and the promotion management data represented by the bars 208, 209, and 210) created in the first example, and the resulting distribution content is stored in the distribution content storage unit 12.

[0123] The operator then uses the GUI input unit 15 to double-click the "management track 2" 211 where the full-package management data (bar 212) is placed on the GUI screen. In response, the replay unit 17 reads the above-described ~~above~~ distribution content which is stored in the distribution content storage unit 12 so as to replay ~~for replaying~~ the content body by following the full-package management data. Note that the terminal 4 side cannot replay the distribution content unless the fee is actually paid. The creating apparatus 1 side, however, preferably replays the content body as if the fee is paid and not paid so as to check ~~for checking~~ whether the above-created distribution content will be replayed correctly by following the management data or for just trying the distribution content so as to check such distribution content ~~for check~~.

[0124] As such, in the present example, a plurality of

management tracks (207, 211, and 213) are provided for the single content track 205 on the GUI screen. Therefore, a plurality of pieces of management data corresponding to the respective use purposes can be set to a single content body. Such plurality of pieces of management data may include, for example, the promotion management data corresponding to the bars 208 to 210, and the full-package management data corresponding to the bar 212. Thus, it is possible to edit the plurality of pieces of management data corresponding to the respective use purposes on the same screen, thereby enabling the operator to efficiently edit the management data.

**[0125]** Also, the plurality of pieces of management data are provided to a single content body to form a package, and the package is stored as a single distribution content. Therefore, the storage amount of the distribution content storage unit 12 can be saved. Note that, in the conventional ~~art~~ apparatuses and methods, when a single content body is distributed for a promotion purpose and a full-package purpose, two distribution contents have ~~has~~ to be stored, one content including the content body and promotion management data and the other content including the content body and full-package management data. Thus, the same content body has to be redundantly stored, thereby wasting the storage amount.

**[0126]** ~~{Third Example ~~example~~}~~

With reference to FIGS. 3, 10 and 11, described below is a case of creating a distribution content including a content



body which is partly provided as a visual effect such as a mosaic and which is incapable of being viewed without the visual effect unless a fee is paid (in other words, the user can see only the video with the mosaic if the fee is not paid, but if paid, can see the video with the mosaic removed therefrom). Such distribution content is hereinafter referred to as a full package with visual effects. In the present example, the distribution content having two pieces of management data, promotion and full-package, as created in the second example, is further provided with management data for the full package with visual effects.

[0127] Similar ~~Similarly~~ to the second example, the operator first selects the distribution content which is stored in the distribution content storage unit 12. The selected distribution content is shown as the bar 206 on the content track 205 of the GUI screen (refer to FIG. 10). Also, the promotion management data which are represented by the bars 208, 209, 210 are shown on the "management track 1" 207, and the full-package management data which is represented by the bar 212 is shown on the "management track 2" 211.

[0128] The operator then uses the GUI input unit 15, by clicking the "button 3" 202 on the GUI screen so as to make ~~for making a~~ new "management track 3" 213 be displayed for the management data for the full package with visual effect. In a similar manner to that in the first example, the operator then clicks the "button 1" 200 on the GUI screen for making the character screen (refer

to FIG. 11) be displayed on the display unit 16, and inputs replay conditions for the respective fields. In this case, the distribution content is a full package with visual effects, meaning that a fee is charged only for a section with the visual effects.

5 Therefore, for the section with visual effects, the operator inputs "conditional replay; visual effects removed" as the replay condition, a fee ("200 yen", for example) as the billing condition, and also the start time (0) and the end time (t7) of that section. Furthermore, for the remaining section, that is, the section

10 without visual effects, the operator inputs "unconditional" as the replay condition, "free" as the billing condition, and also the start time (t7) and the end time (end) of that remaining section. Based on the inputted management data, bars ~~bars~~ 214 and 215 which are each defined by the start time and the end time are displayed

15 on the "management track 3" 213.

[0129] The above-edited management data for the full package with visual effects represented by the bars 214 and 215 are added to the distribution content (including the content body, the promotion management data represented by the bars 208, 209, and

20 210, and the full-package management data represented by the bar 212) as created in the second example, and the resulting distribution content is stored in the distribution content storage unit 12.

[0130] The operator then uses the GUI input unit 15, by clicking

25 the "management track 3" 213 where the bar representing the

management data for the full package with visual effects is placed on the GUI screen. In response, the replay unit 17 reads the above-described ~~above~~-distribution content from the distribution content storage unit 12 so as to replay ~~for replaying~~ the content body by following the management data which are represented by the bars 214 and 215 for the full package with visual effects. Note that the terminal 4 side cannot replay the distribution content without the visual effects unless the fee is actually paid. The creating apparatus 1 side, however, replays the content body as if the fee is paid (a replay with the visual effects) and not paid (a replay with the visual effects), ~~for checking~~ so as to check whether the above-created distribution content will be replayed correctly by following the management data or for just trying the distribution content ~~for check~~ so as to check such distribution content.

[0131] As such, in the present example, the content body is partly provided with visual effects such as a mosaic, and is then provided with management data which is edited for replaying the entire content body without the visual effects after the fee is paid. The distribution content creating apparatus 1 can arbitrarily increase the number of pieces of management data that are provided to the content body, thereby achieving various use purposes.

[0132] ~~(Fourth Example example)~~

With reference to FIGS. 10 and 12, described below is

a case of reusing the management data previously edited and stored for one distribution content so as to create another distribution content. In this example, the promotion management data edited in the first example and stored in the management data storage part 132 is reused.

[0133] The content storage unit 11 stores a plurality of content bodies including the content body which is distributed in the first example. The management data storage part 132 stores the management data 208 which is edited in the first example.

10 The operator first selects a content body for distribution, which is different from the content body ~~that~~ distributed in the first example. Based on the selected content body, the bar 206 is displayed on the content track 205 in the GUI screen (refer to FIG. 10) which is displayed on the display unit 16.

[0134] The operator then uses the GUI input unit 15 such as the mouse 107 to click the "button 3" 202 on the GUI screen, ~~making~~ so as to make the "management track 1" 207 be displayed for placing the bar representing the management data. The operator also clicks the "button 4" 203, ~~making~~ so as to make a table as shown in FIG. 12 be displayed, where the table contains ~~containing~~ data (management data which was previously edited) stored in the management data storage part 132. The operator then clicks the management data corresponding to the bar 208 which is edited in the first example on that table for selection. The selected

management data corresponding to the bar 208 is copied to the "management track 1" 207, and another bar is displayed thereon based on the copied management data.

**[0135]** Note that, in the first example, the operator clicks the "button 1" 200 to make the character input screen be displayed as shown in FIG. 11, and inputs use conditions at the time of content distribution. In the fourth example, such character input can be omitted.

**[0136]** As described above, in the present example, in addition to the distribution content (including the content body, the management track data, and the management data), only the management data is stored in the management data storage unit 132, and reused at the time of creating another distribution content. Thus, character inputs such as the start and end times and replay conditions can be omitted.

**[0137]** Note that, in the first example, portions where no management data is provided on the "management track 1" 207 cannot be replayed. Alternatively, such portions may be provided with management data indicating "unreplayable".

**[0138]** Also, in each of the above-described ~~above~~ examples, the management data is composed of the start time, the end time, the replay condition, the billing condition, and the replay order. In addition, a copy condition may be provided for indicating whether the distributed content body can be copied from the distribution content storage unit 42 of the terminal 4 to the hard disk 105,

for example, of another terminal 4.

**[0139]** While the present invention has been described in detail, the foregoing description is in all aspects illustrative and not restrictive. It is to be understood that numerous other  
5 modifications and variations can be devised without departing from the scope of the present invention.

## ABSTRACT OF THE DISCLOSURE

A distribution content provided with conditions that are only effective to part of a content body is created. On a  
5 time axis ~~204~~, a section ~~t1 to t2~~ of a content body ~~206~~ is specified.  
Management data ~~208~~ is then created, ~~indicating~~ which indicates  
use conditions that are only effective to the specified section,  
and the created management data is provided to the content body  
~~206~~ for distribution.